



## Rubstik Tropic 2335

One Component Contact Adhesive

202402

### DESCRIPTION

Rubstik Tropic 2335 is a one component contact adhesive based on polychloroprene rubber dissolved in organic solvents.

Contact bonding of table top materials of vinyl, linoleum, rubber, plastic laminates such as wood, fiber board, joint filler, rubber, swellable waterstop. The product is also suitable for contact bonding of most common rubber materials and leather.

### USES

- Bond the following items on clean and dry concrete, metal or I-beam surface

TYL-Cell 110

TYL-Cell 100

TYL-Cell 470

TYL-Cell Cork Filler

TYL-HydroStop 1020

TYL-Groove Tape 525

TYL-Buty Rubber Sheet

TYL-SuperSeal T

TYL-High Rubber NP

TYL-Silicone RSB

TYL-Rubber Bearing

TYL-High Rubber EPDM



### ADVANTAGES

- Excellent cold tact
- High heat resistant
- Especially suitable in hot and moist climate

## **PHYSICAL & MECHANICAL PROPERTIES**

<b><u>Property</u></b>	<b><u>Typical Results</u></b>
<b>Ingredients</b>	Polychloroprene rubber and organic solvents
<b>Color</b>	Yellow
<b>Appearance</b>	Viscous liquid
<b>Soil content</b>	22%
<b>Specific gravity</b>	1.13
<b>Viscosity at 23 °C</b>	2500 mPA.s
<b>Open time at 23 °C</b>	5 to 20 mins

## **APPLICATION INSTRUCTIONS**

The materials to be bonded should be dry, clean and free from grease. Grind if necessary.

Before use, the adhesive is stirred until completely homogenous. When adhesive unevenly with trowel or brush to both surfaces. When the adhesive is dry (after approximately 5 mins), the materials are pressed together before expiry of the open time (20 mins).

## **PACKAGING**

5 gallon tin (18.9 liter tin)

## **COVERAGE**

2.5 m<sup>2</sup> per liter

## **STORAGE**

It should be stored in the dry and not left exposed to the elements for extended periods, especially in hot climates.

## **Please enquire about our range of construction product**

The information and the recommendations relating to the application and end use if this product are given in good faith and are based on the information provided by the manufacturer of the product and/or the Company's current knowledge and experience in connection with the product when properly stored, handled and applied under normal conditions and no liability if final function at the job site is assumed. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability of or fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written and/ or oral recommendations, or from any other advice offered by the Company. No responsibility or Liability by the Company will be accepted for misuse, misreading or derivation from the recommended guidelines in respect of this product and the user shall determine the suitability of the product for his intended use and all risks and liability in connection therewith. The information contained in this brochure may change at any time without notice.