

TYL[®]- Silicone RSB

Silicone Rubber Setting Block

DESCRIPTION

TYL-Silicone RSB is a silicone setting block which made of commercial grade solid rubber and are available in a range of material thicknesses and sizes



SPECIFICATION COMPLIANCE

- ASTM C864
- ASTM C542
- BS 4255 Part I

Size

Dimension is an available upon request

PHYSICAL & MECHANICAL PROPERTIES

Property	Typical Results
Density (kg/m³)	1250
	(is an available upon request)
Tensile Strength (MPa)	5.5
Elongation (%)	280
Elongation at Break (%)	20
Shore A Hardness	62 ±5

*Special physical & mechanical properties are an available upon request

Please enquire about our range of construction product

The information and the recommendations relating to the application and end use if this product are given in good faith and are based on the information provided by the manufacturer of the product and/or the Company's current knowledge and experience in connection with the product when properly stored, handled and applied under normal conditions and no liability I final function at the job site is assumed. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability of rom any or a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written and/or or al recommended guidelines in respect of this product and the user shall determine the suitability of the product for his intended use and all risks and liability in connection therewith. The information contained in this brochure may change at any time without notice.