



TYL[®] - Wire Netting

Galvanized/ Stainless Steel Mesh

202402

PHYSICAL & MECHANICAL PROPERTIES TABLE

| Reference No. | | Diameter | | Pitch | | Sheet Size | | Weight (kg/m ²) |
|------------------|-----------------|----------|-------|----------|-----------|------------|------------|--------------------------------|
| Galvanized Steel | Stainless Steel | Main | Cross | Main (A) | Cross (B) | Width (W) | Length (L) | |
| | | (mm) | (mm) | (mm) | (mm) | (Metre) | (Metre) | |
| 21G | 21S | 4 | 3 | 50 | 25 | 2.1 | X 3.6 | 4.18 |
| 210G | 210S | 3 | 3 | 50 | 50 | 2.1 | X 3.6 | 2.2 |
| 228G | 228S | 4 | 4 | 50 | 50 | 2.1 | X 3.6 | 3.96 |
| 31G | 31S | 4 | 3 | 75 | 25 | 2.1 | X 3.6 | 3.52 |
| 310G | 310S | 3 | 3 | 75 | 75 | 2.1 | X 3.6 | 1.46 |
| 3110G | 3110S | 3 | 3 | 75 | 25 | 2.1 | X 3.6 | 2.93 |
| 310aG | - | 3.2 | 3.2 | 75 | 75 | 2.1 | X 3.6 | 1.68 |
| 410G | 410S | 3 | 3 | 100 | 100 | 2.1 | X 3.6 | 1.11 |
| 48G | 48S | 4 | 4 | 100 | 100 | 2.1 | X 3.6 | 1.98 |
| 1111G | 1111S | 3 | 3 | 25 | 25 | 2.1 | X 3.6 | 4.4 |
| 1112G | 1112S | 2.7 | 2.7 | 25 | 25 | 1.2 | X 2.1 | 3.64 |
| 3315 * | - * | 1.5 | 1.5 | 75 | 75 | 1.8 | X 30.0 | 0.36 |
| D31 * | D31S * | 2 | 2 | 100 | 100 | 1.8 | X 60.0 | 0.5 |
| E31 * | E31S * | 2 | 2 | 50 | 50 | 1.8 | X 30.0 | 0.99 |
| D49 * | D49S * | 2.5 | 2.5 | 100 | 100 | 1.8 | X 50.0 | 0.77 |
| E49 * | E49S * | 2.5 | 2.5 | 50 | 50 | 1.8 | X 20.0 | 1.54 |
| E49a (2212) * | E49aS * | 2.7 | 2.7 | 50 | 50 | 1.8 | X 20.0 | 1.8 |
| 1520G * | 1520S * | 1.5 | 1.5 | 20 | 20 | 0.9 | X 30.0 | 1.4 |
| GL-12 ** | - | 0.5 | 0.5 | 12.75 | 12.75 | 0.9 | X 30.0 | 0.28 |
| GL-25 ** | - | 0.9 | 0.9 | 25.4 | 25.4 | 0.9 | X 50.0 | 0.46 |
| GL-50 ** | - | 0.9 | 0.9 | 50.8 | 50.8 | 0.9 | X 50.0 | 0.22 |

Remark: (1)***Types of mesh are supplied in form of rolls.

(2)***Hexagonal Wire Netting.

(3)Stainless Steel Mesh is supplied in grade of AISI 304 and AISI 316.

